

# (12) UK Patent Application (19) GB (11) 2 377 976 (13) A

(43) Date of A Publication 29.01.2003

(21) Application No 0214701.5

(22) Date of Filing 26.06.2002

(30) Priority Data

(31) 60302162 (32) 29.06.2001 (33) US

(71) Applicant(s)

ABB Vetco Gray, Inc  
(Incorporated in USA - Delaware)  
3010 Briarpark Drive, Houston, TX 77042,  
United States of America

(72) Inventor(s)

Thomas F Sweeney (deceased)  
Norman Brammer  
George Chalmers

(74) Agent and/or Address for Service

Lloyd Wise, McNeight & Lawrence  
Regent House, Heaton Lane, STOCKPORT,  
Cheshire, SK4 1BS, United Kingdom

(51) INT CL<sup>7</sup>

F16J 15/08 // E21B 33/03

(52) UK CL (Edition V )

F2B B1E  
E1F FJP

(56) Documents Cited

GB 2363829 A GB 2156918 A

(58) Field of Search

UK CL (Edition T ) E1F FJP, F2B  
INT CL<sup>7</sup> E21B 33/03 33/04, F16J 15/06 15/08  
Other: Online WPI, EPODOC, JAPIO

(54) Abstract Title

**A metal seal for a well-head assembly**

(57) A metal seal ring 43 for a well-head assembly 11, 25 has upper and lower legs 44, 46 extending in opposite directions from each other and a rib 53 extending radially outward from a junction of the legs to give the ring a T-shaped cross-section. A first conical band 47 on the upper leg 44 extends uninterrupted from the rib 53 a selected distance toward a tip of the upper leg 44. A second conical band 45 on the upper leg 44 extends uninterrupted from the tip of the upper leg 44 toward the first conical band 47. An annular recess 49 is located between the first and second conical bands 47, 45. The lower leg 46 also has two conical seal bands separated by a recess.






Fig. 1

GB 2 377 976 A





*Fig. 1*



*Fig. 2*

*Fig. 3*





*Fig. 4*

1                                   **GASKET WITH MULTIPLE SEALING SURFACES**

2                   This application claims priority from the provisional application Serial No.  
3   60/302,162. filed June 29, 2001 entitled "Gasket with Multiple Sealing Surfaces".

4   **Technical Field**

5                   The present invention relates in general to metal-to-metal seals, and in  
6   particular to an improved gasket for sealing between a wellhead housing and a  
7   wellhead connector.

8   **Description of the Prior Art**

9                   In oil and gas wellhead assemblies, tubular members are connected end-to-end  
10   and sealed by a gasket or seal ring. One type of seal ring, particularly used in subsea  
11   wellhead assemblies, is of metal and has upper and lower legs. A rib extends radially  
12   outward from a junction of the legs. Each leg has a conical sealing surface that  
13   engages a conical seat on one of the wellhead members. The conical sealing surface  
14   is a continuous cone that extends from the tip of the leg to the rib. The taper angle of  
15   the sealing surface is typically slightly different than the taper angle of the seat,  
16   creating an interference metal-to-metal sealing engagement. A coating, such as a  
17   silver alloy, may be applied to the sealing surface to enhance sealing.

18                  This type of seal works well. However, improvements are desired in the  
19   ability of the seal to seal against high pressure gas over long periods of time.

20   **Summary of the Invention**

21                  The seal of this invention has two oppositely extending legs and a rib  
22   extending radially from the junction of the legs. A pair of sealing bands are located  
23   on at least one of the legs. The sealing bands are separated by an annular recess. One  
24   of the sealing bands extends from the tip of the leg to the recess. The other extends  
25   from the rib to the recess.

26                  Preferably, the bands are located in the same conical surface of revolution.  
27   The taper angle is slightly smaller relative to the axis of the seal ring, than the seat.  
28   This causes greater contact pressure in the sealing band located adjacent the tip than  
29   the one next to the rib. A coating of molybdenum sulfide is applied to the sealing

1 bands in the preferred embodiment. The recess has tapered upper and lower edges,  
2 and in the preferred embodiment, has a concave base.

3 Preferably, both legs are identical. However, one version of the seal has a  
4 contingent seal leg in the event the conical seat on the lower tubular member is  
5 damaged. The contingent seal leg has only a single sealing band, and it is located  
6 adjacent the tip and separated by a support section. The contingent seal band is at a  
7 much steeper angle, relative to the axis of the seal ring, than the two seal bands on the  
8 opposite leg.

### 9 Brief Description of Drawings

10 Figure 1 is a sectional side view of a seal constructed in accordance with the  
11 present invention and shown installed between a wellhead housing and a wellhead  
12 connector.

13 Figure 2 is an enlarged sectional view of the seal of Figure 1.

14 Figure 3 is an a further enlarged sectional view of a portion of the seal of  
15 Figure 1.

16 Figure 4 is a sectional view of an emergency embodiment of the seal of Figure  
17 1.

### 18 Detailed Description of the Preferred Embodiment of the Present Invention

19 Referring to Fig. 1, wellhead housing 11 has a bore 13 terminating on its upper  
20 end in a rim with an upward facing shoulder 17. A conical primary seat or sealing  
21 surface 19 extends downward and inward from shoulder 17. Primary seal surface 19  
22 has a lower marginal edge that joins a secondary seat or seal surface 21. Secondary  
23 seal surface 21 is preferably conical, also, but at a lesser angle relative to the axis of  
24 bore 13 than primary seal surface 19. The lower marginal edge of secondary seal  
25 surface 21 joins a transition surface 23. The axial extent of secondary seal surface 21  
26 is less than the axial extent of primary seal surface 19 in the preferred embodiment.  
27 Transition surface 23 is a conical surface with a lower edge that joins bore 13.

28 A wellhead connector 25 will connect to wellhead housing 11. Wellhead  
29 connector 25 has a lower portion that slides over the exterior of wellhead housing 11.  
30 Wellhead connector 25 has a locking member such as dogs (not shown) that are  
31 moved into engagement with grooves (not shown) formed on the exterior of wellhead

1 housing 11. Wellhead connector 25 has a bore 33 that is coaxial with bore 13. A  
2 downward facing shoulder 35 of wellhead connector 25 contacts and bears against  
3 shoulder 17 of wellhead housing 11. A recess 37 is located radially inward from  
4 downward facing shoulder 35. Recess 37 has an outer wall 38 that is cylindrical and  
5 coaxial with wellhead connector bore 33. A conical seat or sealing surface 39 extends  
6 upward and inward from recess 37. Conical surface 39 has an upper marginal edge  
7 that joins a transition shoulder 41. Transition shoulder 41 is perpendicular to the axis  
8 of bore 33.

9 A gasket or seal ring 43 locates between wellhead connector 25 and wellhead  
10 housing 11. Seal ring 43 is generally T-shaped, and in this embodiment has an upper  
11 end or leg 44 and a lower leg or end 46 that are symmetrical. Each portion has a first  
12 seal band 45 near one end and a second seal band 47 spaced from seal band 45 by a  
13 recess 49. A rib 53 extends radially outward on the exterior of seal ring 43. Rib 53  
14 locates in recess 37, with the outer side of rib 53 located inward from recess outer  
15 wall 38.

16 Each first seal band 45 extends from a tip of its seal leg 44 or 46 toward rib  
17 53. Each second seal band 47 extends from rib 53 toward the tip of its seal leg 44 or  
18 46. In the preferred embodiment, recess 49 is located midway between the tip of each  
19 leg 44 or 46 and rib 53. Each seal band 45, 47 is substantially the same width in this  
20 embodiment. Recess 49 has a width that is selected to increase the contact pressures  
21 of seal bands 45, 47 against their seats. However, the widths of the seal bands 45, 47  
22 should be sufficiently large so as to avoid any leakage due to small scratches in the  
23 seal bands 45, 47 or seats that occur during installation. Preferably the width of each  
24 band 45, 47 is several times the width of recess 49. As shown in Fig.3, preferably the  
25 upper and lower edges of recess 49 are tapered. Also, recess 49 is preferably a  
26 continuous curved surface, having a concave base 49a formed at a radius. Recess 49 is  
27 fairly shallow, having a depth that is less than its width.

28 Seal ring 43 is of metal and is constructed so that its seal bands 45, 47  
29 interferingly engage conical surfaces 39 and 19. The interference causes elastic and  
30 permanent yielding when wellhead connector 25 connects to wellhead housing 11.  
31 The elastic yielding of seal ring 43 provides the necessary sealing between seal bands  
32 45, 47 and conical seats 39 and 19.



1 In the embodiments of Figs. 1 and 2, each seal band 45, 47 is at the same  
2 conical angle relative to the axis of seal ring 43 and on the same conical surface of  
3 revolution. This conical angle, however, is preferably slightly different from the  
4 angle of its seat 39 or 19 so as to create more contact stress on the first conical band  
5 45 than the second conical band 47. Referring to Figures 1 and 2, the angle 51 is  
6 smaller relative to the axis of seal ring 43 than the angles of seats 39 and 19 of  
7 wellhead members 25 and 11. Suitable angles 51 are in the range from 22 to 45  
8 degrees.

9 Referring again to Fig. 3, the metal body of seal ring 45 is preferably of high  
10 strength metal, such as a stainless steel having a yield strength at least from 35 to 40  
11 thousand pounds per square inch. A coating 55 is formed on seal bands 45, 47 in  
12 order to enhance sealing. Although shown on recess 49, the coating on recess 49  
13 serves no sealing purpose. Coating 55 is preferably molybdenum sulfide. In the  
14 preferred method, seal bands 45, 47 are finished to a high degree of smoothness, such  
15 as 8 RMS, then thoroughly cleaned. The molybdenum sulfide is coated on the  
16 smooth surface without sand blasting the underlying metal. This provides a very  
17 smooth surface finish.

18 Figure 4 shows a contingent gasket 81 in the event that primary seal surface 19  
19 of wellhead housing 11 becomes damaged. Seal ring 81 has an upper seal surface that  
20 is the same as in the other embodiments. It has a first seal band 84 and a second seal  
21 band 86 separated by a recess 83. The lower leg, however differs and may be  
22 constructed as shown in US Pat 5,103,915. The lower leg has a support section 85  
23 that extends downward, overlying primary seal surface 19. Support section 85 is  
24 conical, at the same inclination as primary seal surface 19, however may be at a lesser  
25 dimension so that it does not touch. This results in a gap between support section 85  
26 and the damaged primary sealing surface 19. Under load, a portion of support section  
27 85 will deflect and touch primary seal surface 19, but not enough to cause sealing.

28 A lower seal surface 89 extends downward from support section 85. Lower  
29 seal surface 89 inclines relative to the axis of bore 13 at the same inclination as  
30 secondary seal surface 21. It is sized at a greater diameter so as to create an  
31 interference fit with secondary seal surface 21. Seal ring 81 has an inner diameter  
32 with an upper portion 91a that is conical and leads to a central portion 91b that is



1 cylindrical. Central portion 91b leads to a lower portion 91c that is conical. Central  
2 portion 91b is of greater diameter than upper and lower portions 91a, 91c. This  
3 provides a recessed or concave inner diameter to assist in the flexibility of seal ring  
4 81.

5 The invention has significant advantages. Tests have shown that a seal  
6 constructed as above was able to withstand more stringent pressure tests than prior art  
7 seals having only a single seal band and no recess. This is particularly important for  
8 deepwater subsea well installations.

9 While the invention has been shown in only two of its forms, it should be  
10 apparent to those skilled in the art that it is not so limited but is susceptible to various  
11 changes without departing from the scope of the invention. For example, although the  
12 discussion above deals with permanent or plastic deformation of the seal ring, it is  
13 also applicable to metal seal rings designed for elastic deformation.

- 1 We claim:
- 2 1. A metal seal, comprising:
- 3 a ring having first and second legs extending in opposite directions and a rib
- 4 extending radially outward from a junction of the legs;
- 5 a sealing surface on an exterior portion of each of the legs;
- 6 the sealing surface on the first leg being a pair of conical bands separated by a
- 7 recess.
- 8
- 9 2. The seal according to claim 1, wherein one of the bands extends substantially from
- 10 the rib to the recess, and the other of the bands extends substantially from the tip of
- 11 the first leg to the recess.
- 12
- 13 3. The seal according to claim 1, wherein the recess has upper and lower tapered
- 14 edges.
- 15
- 16 4. The seal according to claim 1, wherein each of the bands has a width that is greater
- 17 than a width of the recess.
- 18
- 19 5. The seal according to claim 1, wherein each of the bands is inclined at the same
- 20 conical angle.
- 21
- 22 6. The seal according to claim 1, wherein each of the bands is located in the same
- 23 conical surface of revolution.
- 24
- 25 7. The seal according to claim 1, wherein:
- 26 a first one of the bands extends substantially from a tip of the first leg;
- 27 a second one of the bands extends substantially from the rib; and
- 28 each of the bands is inclined at the same conical angle, and the conical angle is
- 29 selected to differ from a seat angle so as to cause greater contact pressure in the first
- 30 one of the bands than the second one of the bands.
- 31

- 1 8. The seal according to claim 1, wherein the sealing surface on the second leg  
2 comprises a contingent seal band extending from a tip of the second leg toward the rib  
3 and separated from the rib by a support surface that is at a substantially different angle  
4 relative to the contingent seal band.  
5
- 6 9. The seal according to claim 1, further comprising a coating on each of the bands of  
7 molybdenum sulfide.  
8
- 9 10. A metal seal, comprising:  
10 a ring having upper and lower legs extending in opposite directions from each  
11 other and a rib extending radially outward from a junction of the legs;  
12 a first conical band on the upper leg extending uninterrupted from the rib a  
13 selected distance toward a tip of the upper leg;  
14 a second conical band on the upper leg extending uninterrupted from the tip of  
15 the upper leg toward the first conical band; and  
16 an annular recess located between the first and second conical bands.  
17
- 18 11. The seal according to claim 10, wherein a width of the recess is less than a width  
19 of the first conical band and less than a width of the second conical band.  
20
- 21 12. The seal according to claim 10, wherein the first and second conical bands are  
22 located in the same conical surface of revolution.  
23
- 24 13. The seal according to claim 10, wherein:  
25 the first and second conical bands are located at the same conical angle in the  
26 same conical surface of revolution; and  
27 the conical angle is selected to differ from a seat angle so as to cause a greater  
28 contact pressure of the second conical band than the first conical band.  
29
- 30 14. The seal according to claim 10, wherein the recess has upper and lower tapered  
31 edges and a concave base.

- 1 15. The seal according to claim 10, wherein the lower leg has a contingent seal band  
2 extending from a tip of the lower leg toward the rib and separated from the rib by a  
3 support surface that is at a substantially different angle relative to the contingent seal  
4 band.  
5
- 6 16. The seal according to claim 10, further comprising a coating on each of the bands  
7 of molybdenum sulfide.  
8
- 9 17. The seal according to claim 10, further comprising:  
10 a third conical band on the lower leg extending uninterrupted from the rib a  
11 selected distance toward a tip of the lower leg;  
12 a fourth conical band on the lower leg extending uninterrupted from the tip of  
13 the lower leg toward the third conical band; and  
14 an annular recess located between the third and fourth conical bands.  
15
- 16 18. A well assembly, comprising:  
17 an upper tubular member having a rim and a conical seat located on an inner  
18 surface of the rim;  
19 a lower tubular member having a rim and a conical seat located on an inner  
20 surface of the rim of the upper tubular member;  
21 a seal having an upper leg that has an outer sealing surface that seals against  
22 the seat of the upper tubular member, a lower leg that has an outer sealing surface that  
23 seals against the seat of the lower tubular member, and a rib that extends radially  
24 outward from a junction of the upper and lower legs;  
25 each of the sealing surfaces comprising two conical bands separated by an  
26 annular recess, with one of the conical bands extending from a tip of the leg on which  
27 it is located toward the rib, and the other of the conical bands extending from the rib  
28 toward the tip of the leg on which it is located;  
29 the recess being smaller in width than the conical bands and having tapered  
30 upper and lower edges;  
31 the conical bands being at the same conical angle and in the same conical  
32 surface of revolution;

1       the conical angle of the conical bands being slightly smaller than a conical  
2   angle of each of the seats, relative to an axis of the tubular members, so as to cause a  
3   greater contact pressure with the conical band that begins at the tip than the conical  
4   band that begins at the rib.

5

6   19. The seal according to claim 18, further comprising a coating on each of the  
7   conical bands of molybdenum sulfide.

8



Application No: GB 0214701.5  
Claims searched: 1 to 19

Examiner: Kevin Hewitt  
Date of search: 21 November 2002

## Patents Act 1977 Search Report under Section 17

### Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:  
UK Cl (Ed.T): F2B (B1E); E1F (F1P)  
Int Cl (Ed.7): E21B 33/03, 33/04; F16J 15/06, 15/08  
Other: Online WPI, EPODOC, JAPIO

### Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	GB 2363829 A (SHARP) See especially Figs. 2, 4 and 5.	1-6
X	GB 2156918 A (NUOVO PIGNONE) See especially metal ring 9 and recesses 10 in Fig.2.	1-6

10

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.